



securitysalesmanager@caddx.us

www.caddx.us +1(315) 409719

Head Office and R&D Team:
Add: 314 East Fayette Street,
Syracuse, NY, USA 13202

CADDX SYSTEMS INC.

NVR6CH /5MP/1HDD



CA-806NVR

Features :

1. Support H.265+/H.265/H. 264
2. Support 5M , 4 M, 2M
3. VGA, HDMI output simultaneously
4. **NEW TECHNOLOGY**Support **NEW Smart function** for industrial refrigerators temperatures, humidity, controls Gates, **Others**....
5. Cloud service www.caddxcloud.net , support Google cloud server, P2P, Alarm pushing
6. Multiple network services DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI
7. cell phone access supported (IOS, Android) caddx.us.smart
8. IE internet explorer Browser access supported
9. More than twenty kind of language
10. Multiple platform : WEB, CMS, VMS, Caddx APP

Technical Parameters :

Model number		CA-806NVR
System	Main processor	HI3536D-2G
	OS	Embedded LINUX
	Build in POE	NOT SUPPORTED
	PROTOCOLS	ONVIF / CADDX PROTOCOLS
Video	VIDEO INPUT	6ch*5M /25fps -9ch*1080p/25fps
	Video compression	H.265+/H.265/H.264
	Video standards	PAL /NTSC
	DISPLAY QUALITY	MAX:4K,5MP,4MP,2MP
	MOTION DETECTION	Depend in the camera
RECORD & PLAY BACK	Record Mode	Manual>Alarm>Motion detection>Timing
	Record Query	Time point、Calendar、Event、Chanel
	Record storage	Local hard disk、Network
	Playback	Main stream playback: 2*5M /25fps, Sub-stream playback: 9*D1/25fps
	Backup Mode	Network、USB HARD disk, USB BURNER
Interface	Video output	1*HDMI, 1*VGA
	NETWORK INTERFACE	1*RJ45 10M/100M/1000M self -Adaptive
	AUDION I/O	NOT SUPPORTED
	USB INTERFACE	2*USB2.0
Others	PTZ CONTROL	CONTROL PTZ Devices by network
	HDD	1*SATA (each max 8T)
	Power Supply	12V 3A
	Working temperature	0°C- +55°C
	Working Humidity	10%--90%
	Size	255mm (Length) *215mm (Width) 40mm (Height)
	WEIGHT	Around 220g