



securitysalesmanager@caddx.us www.caddx.us +1(315) 409719 Head Office and R&D Team:
Add: 314 East Fayette Street,
Syracuse, NY, USA 13202

CADDX SYSTEMS INC.

4 IN 1 PTZ DOME



CA-NM55XHD/4

Specification :

* 2MP / high speed dome with OSD, 5X
* IR distance up to 45 m / 4pcs LED
* PTZ Control Protocol RS485 COAXIAL FUNCTION, IP66
* Pan 355-degree Tilt 70 degree
* Pan speed: 25°/s; Tilt speed: 20°/s
* Manual speed High, medium, low (adjustable)

Model	CA-NM55XHD/4
Zoom module	
Resolution	2MP
Chipset + sensor	NVP2477+OV05A10
Lens	5X
WB	Auto/Indoor/Outdoor/Manual
IP	66
Min.Illumination	Color: 0.08Lux @ (F1.4, AGC ON), B/W: 0.05Lux @(F1.4, AGC ON), 0 Lux with IR
White balance	auto / manual / auto-tracking/outdoor/indoor/fluorescent lamp/sodium lamp
Gain control (AGC)	auto/manual
SNR	More than 50dB
Noise reduction	3D&2D
WB	Auto/Indoor/Outdoor/Manual
BLC	ON/OFF
WDR	Support
Shutter	1/1-1/30,000s
Day/night mode	Auto ICR color to black
Focus mode	Auto /semi-auto /manual
Focal length	5.1~51mm, 10x optical
Zoom speed	About 3 sec. (optical, wide angel-telescope)
Horizontal view angel	52° (wide angel-telescope)
Close-up	10-1000mm(wide angel-telescope)
Function	

IR distance	Up to 45 meters
LEDs	4pcs LED
IR angle	Adjustable
Pan speed	25°/s
Pan range	355 degree
Rotation Range	Pan:0°~200° , Tilt:~45°~40°
Rotation Speed	Pan:0~30°/s , Tilt:0~25°/s
Auto Flip	Support
Preset Points	220pcs preset(Dwell time 01-60s interval available)
Guard Tours	3 groups (each group 16 preset, dwell time and speed selectable)
AB scan range	Any point in range:-45°~40° and 0°~200°
AB scan speed	1-9 grades
Tilt speed	20°/s
Tilt range	70 degree
Manual speed	High, medium, low (adjustable)
Proportional Zoom	Support
Number of Preset	256
Patrol	4
Pattern	1
Scan between two presets	Support
Park Action	presets/pattern/patrol/scan between two presets/ auto
Area-limit	Support
Video out	AHD,BNC connector, PAL/NTSC
Others	

PTZ control protocol	RS485
Power Supply	DC 12V
Power Consumption M	≤15W
Working Temperature/Humidity	-40°C~+60°C, hUMIDITY10%~90%
Protection Grade	TVS3000V lightning protection, surge protection and voltage transient protection, weather proof: IP66
UTC control	support control via coaxial cable

Weight (g) 550g

Dimension 155(W)×145(H)×305(D)

