



securitysalesmanager@caddx.us www.caddx.us +1(315) 409719 Head Office and R&D Team:
Add: 314 East Fayette Street,
Syracuse, NY, USA 13202

CADDX SYSTEMS INC.

Day & Night IR AHD Camera



Specification :

| | |
|---------------------------|---------------------------------------|
| Model | CA-NH296HD |
| Pick up Element | AHD/TVI/CVI/CVBS |
| Image Sensor | 2MP CMOS SENSOR |
| Video uncompressed format | AHD/TVI/CVI/CVBS |
| Effective Picture | 2010(H) X 1108(V) 1944(H)* 1092(V) |
| Elements(H*V) | 1944(H)* 1092(V) |
| Real-time Resolution | 2MP |
| Minimum Illumination | 0.001Lux(with24LED /12U) |
| OSD Menu | OSD/UTC/CVBS |
| Video Output | 750hm BNC*2 |
| Lens Type | Fixed lens |

| | |
|----------------------------------|--|
| Lens | 3.6 MM / 3MP |
| Auto Electronic Shutter | Manual/Auto: 1/50s~1/100,000s |
| Synchronous System | Internal |
| White balance | ATW/Manual/Outdoor/Indoor/AWC |
| NR (noise reduction) | 2-DNR/ 3-DNR/ SMART NR |
| Digital effect | Freeze, Mirror, D-zoom, Neg, Image |
| DWDR | High/ Middle/ Low |
| BLC | BLC/HLC/OFF |
| Lens shading compensation | ON/OFF |
| Day&Night | Auto/ Manual/ Color/EXT |
| Power/ Current | 12V DC (±10%) |
| AHD transmission range | 400 meters, use standard coaxial cable (RG59) with BNC interface |
| Led Range | 35 meters |
| operating Temperature | -20~75°C |

