



securitysalesmanager@caddx.us www.caddx.us +1(315) 409719 Head Office and R&D Team:  
Add: 314 East Fayette Street,  
Syracuse, NY, USA 13202

# CADDX SYSTEMS INC.

## Day & Night IR AHD Camera



### Specification :

|                           |                                       |
|---------------------------|---------------------------------------|
| Model                     | CA-NBD260HD                           |
| Pick up Element           | AHD/TVI/CVI/CVBS                      |
| Image Sensor              | 2MP CMOS SENSOR                       |
| Video uncompressed format | AHD/TVI/CVI/CVBS                      |
| Effective Picture         | 2010(H) X 1108(V)<br>1944(H)* 1092(V) |
| Elements(H*V)             | 1944(H)* 1092(V)                      |
| Real-time Resolution      | 2MP                                   |
| Minimum Illumination      | 0.001Lux(with3LED /28μ)               |
| OSD Menu                  | OSD/UTC/CVBS                          |
| Video Output              | 750hm BNC*2                           |

|                                  |  |
|----------------------------------|--|
| <b>Lens Type</b>                 | FIXED lens   |
| <b>Lens</b>                      | 3mp /3.6mm   |
| <b>Auto Electronic Shutter</b>   | Manual/Auto: 1/50s~1/100,000s                                    |
| <b>Synchronous System</b>        | Internal   |
| <b>White balance</b>             | ATW/Manual /Outdoor/In door/AWC                                  |
| <b>NR( noise reduction)</b>      | 2-DNR/ 3-DNR/ SMART NR   |
| <b>Digital effect</b>            | Freeze, Mirror, D-zoom, Neg , Image                              |
| <b>WDR</b>                       | High SUPPORT 120dB   |
| <b>BLC</b>                       | BLC/HLC/OFF  |
| <b>Lens shading compensation</b> | ON/OFF   |
| <b>Day&amp;Night</b>             | Auto/ Manual/ Color/EXT  |
| <b>Power/ Current</b>            | 12V DC (±10%)  |
| <b>AHD transmission range</b>    | 400 meters, use standard coaxial cable (RG59) with BNC interface |
| <b>Led Range</b>                 | 25 meters  |
| <b>operating Temperature</b>     | -20~75°C   |

