



securitysalesmanager@caddx.us www.caddx.us +1(315) 409719 Head Office and R&D Team:
Add: 314 East Fayette Street,
Syracuse, NY, USA 13202

CADDX SYSTEMS INC.

19 Port 10/100/1000M POE Switch-(16+3)

Model No.:CA-1621GB (Support 1U Standard rack)

Product Describe

The POE switch provides power and data from a single point, using Power over Ethernet (POE) over a single Cat-5 cable. It can be used for any 10/100/1000Mbps link and supply industry-standard IEEE 802.3af power. Advanced auto-sensing algorithm gives power to 802.3af end devices ,In addition ,the POE switch automatically determines POE requirements, speed, duplex, and cable type using Auto Uplink. Easy to operate and reliable.

The POE switch is ideal for powering POE devices such as IP cameras, WLAN access point, IP phones, office access control systems, and other PD devices and offers a line of high quality products that provide a total solution for Ethernet application in different environments.

19 Port 10/100/1000M POE Switch(16+3)



- ◆ 16*10/100mbps POE port,2*10/100/1000mbps UP-Link port,1*SFP
 - ◆ ·100m Transmission Distance,250m after use extend function
 - ◆ ·Compatible with IEEE802.3AF/AT,support:1U Standard rack
 - ◆ ·Whole Power:300W(52V 5.8A)
 - ◆ ·All port supported by MDI/MDIX auto flip and self negotiation
 - ◆ ·Supply 16pcs 10/100Mbps adaptive high speed forwarding data packet non-lost port.
 - ◆ ·Each port max. power supply reached 30W.
 - ◆ Low heat design, safe and reliable, high stability
- Application:↔·Wireless Access Point↔·IP Camera
↔·IP Phone↔·Computer Networks

Technical Specification

Product Name	16 Port 10/100/100M POE Switch(16+3)
Product Model	CA-1621GB
DATA PIN	1/2+,3/6-
Power Supply Type	Build In, Both 1/2+,3/6- and 4/5+7/8-
PoE Output Power	15.4W/30W
Connector	16*10/100mbps POE port,2*10/100/1000mbps UP-Link port,1*SFP

Network Medium	Cat5 (UTP) or more
Technology	
Network Standards	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3x Flow Control IEEE 802.3af Power over Ethernet
POE power	15.4W per port(IEEE802.3af). Wiring: Data & power provided over pairs 1/2 and 3/6 or 4/5 (+) and 7/8(-)
Processing types	Store-and-forward Half-duplex back pressure and IEEE 802.3x full-duplex flow control
Address database Table Size	8K MAC address entry
Buffer memory	48Kb embedded memory per unit
Backboard Bandwidth	8.8G
Network Latency	Less than 20us for 64 byte frames in store-and-forward mode for 100Mbps to 100Mbps transmission
Power	
Input	50V 7A 250W
POE power consumption	15.4W per port(IEEE802.af)
Overload current protection	Present
Mechanical	
Casing	Metal
Installation	Rack mounting
Interface	
LED Indicators	System: Power, POE Maximum power Per port: Link, Activity, Speed, POE active, POE error
Environment specification	
Operating temperature	-10-55°C (32-104°F)
Storage temperature	-40-70°C (14-158°F)
Operating humidity	90% maximum relative humidity, non-condensing
Storage humidity	95% maximum relative humidity, non-condensing
Regulatory Approval	
ISO	Manufactured in ISO9001 facility
Safety	CE/CCC
Warranty	2 years
Dimensions	440*285*55mm (L*W*H)
Weight	3.95Kg

Package List

Package List	16 Port 10/100/1000M POE Switch*1
	User Guide*1
	Warranty Card*1
	Power cable*1
	Bracket*2,Screw*8

Product Details



Application Diagram

